

## 2. TIGHTENING TORQUE

Use following table for unspecified torque.

### 1) BOLT AND NUT

#### (1) Coarse thread

Bolt size	8T		10T	
	kgf · m	lbf · ft	kgf · m	lbf · ft
M 6 × 1.0	0.85 ~ 1.25	6.15 ~ 9.04	1.14 ~ 1.74	8.2 ~ 12.6
M 8 × 1.25	2.0 ~ 3.0	14.5 ~ 21.7	2.73 ~ 4.12	19.7 ~ 29.8
M10 × 1.5	4.0 ~ 6.0	28.9 ~ 43.4	5.5 ~ 8.3	39.8 ~ 60
M12 × 1.75	7.4 ~ 11.2	53.5 ~ 79.5	9.8 ~ 15.8	71 ~ 114
M14 × 2.0	12.2 ~ 16.6	88.2 ~ 120	16.7 ~ 22.5	121 ~ 167
M16 × 2.0	18.6 ~ 25.2	135 ~ 182	25.2 ~ 34.2	182 ~ 247
M18 × 2.5	25.8 ~ 35.0	187 ~ 253	35.1 ~ 47.5	254 ~ 343
M20 × 2.5	36.2 ~ 49.0	262 ~ 354	49.2 ~ 66.6	356 ~ 482
M22 × 2.5	48.3 ~ 63.3	350 ~ 457	65.8 ~ 98.0	476 ~ 709
M24 × 3.0	62.5 ~ 84.5	452 ~ 611	85.0 ~ 115	615 ~ 832
M30 × 3.5	124 ~ 168	898 ~ 1214	169 ~ 229	1223 ~ 1655
M36 × 4.0	174 ~ 236	1261 ~ 1703	250 ~ 310	1808 ~ 2242

#### (2) Fine thread

Bolt size	8T		10T	
	kgf · m	lbf · ft	kgf · m	lbf · ft
M 8 × 1.0	2.17 ~ 3.37	15.7 ~ 24.3	3.04 ~ 4.44	22.0 ~ 32.0
M10 × 1.25	4.46 ~ 6.66	32.3 ~ 48.2	5.93 ~ 8.93	42.9 ~ 64.6
M12 × 1.25	7.78 ~ 11.58	76.3 ~ 83.7	10.6 ~ 16.0	76.6 ~ 115
M14 × 1.5	13.3 ~ 18.1	96.2 ~ 130	17.9 ~ 24.1	130 ~ 174
M16 × 1.5	19.9 ~ 26.9	144 ~ 194	26.6 ~ 36.0	193 ~ 260
M18 × 1.5	28.6 ~ 43.6	207 ~ 315	38.4 ~ 52.0	278 ~ 376
M20 × 1.5	40.0 ~ 54.0	289 ~ 390	53.4 ~ 72.2	386 ~ 522
M22 × 1.5	52.7 ~ 71.3	381 ~ 515	70.7 ~ 95.7	512 ~ 692
M24 × 2.0	67.9 ~ 91.9	491 ~ 664	90.9 ~ 123	658 ~ 890
M30 × 2.0	137 ~ 185	990 ~ 1338	182 ~ 248	1314 ~ 1795
M36 × 3.0	192 ~ 260	1389 ~ 1879	262 ~ 354	1893 ~ 2561

## 2) PIPE AND HOSE(FLARE TYPE)

Thread size(PF)	Width across flat(mm)	kgf · m	lbf · ft
1/4"	19	4	28.9
3/8"	22	5	36.2
1/2"	27	6	43.4
3/4"	36	12	86.8
1"	41	14	101

## 3) PIPE AND HOSE(ORFS TYPE)

Thread size(UNF)	Width across flat(mm)	kgf · m	lbf · ft
13/16-16"	24	4.4	32.5
1-3/16-12"	36	9.3	67.3
1-7/16-12"	41	13.2	95.5
1-11/16-12"	50	18.3	132.4
2-12"	55	22.6	163.5

## 4) FITTING

Thread size(PF)	Width across flat(mm)	kgf · m	lbf · ft
1/4"	19	4	28.9
3/8"	22	5	36.2
1/2"	27	6	43.4
3/4"	36	13	94.0
1"	41	15	109

#### 4) TIGHTENING TORQUE OF MAJOR COMPONENT

No	Items	Size	kgf · m	lbf · ft	
1	Engine	Engine mounting bolt(2EA)	M20×2.5	57.9±8.7	419±62.9
2		Engine mounting bolt(Bracket)	M12×1.75	10.7±1.6	77.4±11.6
3		Radiator mounting bolt	M16×2.0	29.7±4.5	215±32.5
4		Fuel tank mounting bolt	M16×2.0	29.7±4.5	215±32.5
5		Air cleaner mounting bolt	M 8×1.25	2.5±0.5	18.1±3.6
6	Hydraulic system	Main pump housing mounting bolt	M12×1.75	12.8±3.0	92.6±21.7
7		Main control valve mounting bolt	M12×1.75	12.8±3.0	92.6±21.7
8		Steering unit mounting bolt	M10×1.5	6.9±1.4	49.9±10.1
9		Steering valve mounting bolt	M 8×1.25	2.5±0.5	18.1±3.6
10		Brake valve mounting bolt	M 8×1.25	2.5±0.5	18.1±3.6
11		Fan and brake pump mounting bolt	M10×1.5	6.9±1.4	49.9±10.1
12		Cut-off valve mounting bolt	M12×1.75	12.8±3.0	92.6±21.7
13		Remote control lever mounting bolt	M 6×1.0	1.1±0.2	8.0±1.4
14		Pilot supply unit mounting bolt	M 8×1.25	2.5±0.5	18.1±3.6
15		Safety valve	M 8×1.25	2.5±0.5	18.1±3.6
16	Hydraulic oil tank mounting bolt	M16×2.0	29.7±4.5	215±32.5	
17	Power train system	Transmission mounting bolt	M24×3.0	100±15	723±109
18		Transmission mounting bolt(Bracket)	M20×2.5	46.3±7.0	335±50.6
19		Torque converter housing mounting bolt	M10×1.5	4.6±0.7	33.3±5.1
20		Front axle mounting bolt, nut	M24×2.0	100±15	723±109
21		Rear axle support mounting bolt, nut	M27×2.0	135±15	976±108
22		Tire mounting nut	M22×1.5	79±2.5	571±18
23		Drive shaft joint mounting bolt	3/8-24UNF-48	5.95±0.85	43.0±6.1
24	Others	Counterweight mounting bolt	M30×2.0	199±29.9	1439±216
25		Additional counterweight mounting bolt	M24×2.0	100±15	723±108
26		Operator's seat mounting bolt	M 8×1.25	3.4±0.8	24.6±5
27		ROPS Cab mounting bolt(4EA)	M27×2.0	124	900