

## 9. RECOMMENDED OILS

Use only oils listed below or equivalent.  
Do not mix different brand oil.

Service point	Kind of fluid	Capacity l (U.S. gal)	Ambient temperature °C ( °F)								
			-20 (-4)	-10 (14)	0 (32)	10 (50)	20 (68)	30 (86)	40 (104)		
Engine oil pan	Engine oil	17.5 (4.6)				SAE 30					
			SAE 10W								
			SAE 10W-30								
					SAE 15W-40						
Swing drive	Grease	1.2 (0.32)	NLGI NO.1								
					NLGI NO.2						
Swing drive	Gear oil	5.0 (1.3)							SAE 85W-140		
Final drive		5.8 × 2 (1.53 × 2)									
Hydraulic tank	Hydraulic oil	Tank: 160 (42.3) System: 240 (63.4)	ISO VG 32								
					ISO VG 46						
					ISO VG 68						
Fuel tank	Diesel fuel	260 (68.7)	ASTM D975 NO.1								
					ASTM D975 NO.2						
Fitting (Grease nipple)	Grease	As required	NLGI NO.1								
					NLGI NO.2						
Radiator (Reservoir tank)	Mixture of antifreeze and water 50 : 50	15.5 (4.1)	Ethylene glycol base permanent type								

**SAE** : Society of Automotive Engineers  
**API** : American Petroleum Institute  
**ISO** : International Organization for Standardization  
**NLGI** : National Lubricating Grease Institute  
**ASTM** : American Society of Testing and Material