

8. RECOMMENDED OILS

Use only oils listed below or equivalent.
Do not mix different brand oil.

Service point	Kind of fluid	Capacity l (U.S. gal)	Ambient temperature C(F)							
			-20 (-4)	-10 (14)	0 (32)	10 (50)	20 (68)	30 (86)	40 (104)	
Engine oil pan	Engine oil	18.5(4.9)					SAE 30			
Transmission case			3.0(0.8)	SAE 10W						
		SAE 10W-30								
Swing drive	Gear oil	5.0(1.3)					SAE 85W-140			
	Grease	1.2(0.3)	NLGI NO.1							
							NLGI NO.2			
Front axle	Gear oil	Center : 10.5(2.8) Hub : 2.5 l 2(0.7 l 2)					SAE 85W-90			
Rear axle		Center : 15.1(4.0) Hub : 2.5 l 2(0.7 l 2)								
Hydraulic tank	Hydraulic oil	Tank: 160(42.3) System: 270(71.3)	ISO VG 32							
			ISO VG 46							
			ISO VG 68							
Fuel tank	Diesel fuel	260(68.7)	ASTM D975 NO.1							
							ASTM D975 NO.2			
Fitting (Grease nipple)	Grease	As required	NLGI NO.1							
							NLGI NO.2			
Radiator (Reservoir tank)	Mixture of antifreeze and water 50 : 50	30(7.9)					Ethylene glycol base permanent type			

SAE : Society of Automotive Engineers
API : American Petroleum Institute
ISO : International Organization for Standardization
NLGI : National Lubricating Grease Institute
ASTM : American Society of Testing and Material