

8. SPECIFICATIONS FOR MAJOR COMPONENTS

1) ENGINE

Item	Specification
Model	HYUNDAI D6AC-C
Type	4-cycle turbocharged charger air cooled diesel engine
Cooling method	Water cooling
Number of cylinders and arrangement	6 cylinders, in-line
Firing order	1-5-3-6-2-4
Combustion chamber type	Direct injection type
Cylinder bore × stroke	130 × 140mm(5.12" × 5.51")
Piston displacement	11149cc(680cu in)
Compression ratio	17 : 1
Rated gross horse power(SAE J1995)	276Hp at 1900rpm(206kW at 1900rpm)
Maximum torque	120kgf · m(868lbf · ft) at 1400rpm
Engine oil quantity	27.3 l (7.2U.S. gal)
Dry weight	920kg(2028lb)
Low idling speed	800 ± 50rpm
High idling speed	2050+ 50rpm
Rated fuel consumption	157g/Hp · hr at 1900rpm
Starting motor	MANDO VALEO 24V-5.5kW
Alternator	MANDO VALEO 24V-70A
Battery	2 × 12V × 160Ah

2) MAIN PUMP

Item	Specification
Type	Variable displacement tandem axis piston pumps
Capacity	2 × 168.5cc/rev
Maximum pressure	330kgf/cm ² (4690psi)[360kgf/cm ² (5120psi)]
Rated oil flow	2 × 286 l /min (75.5U.S. gpm/ 62.9U.K. gpm)
Rated speed	1700rpm

[]: Power boost

3) GEAR PUMP

Item	Specification
Type	Fixed displacement gear pump single stage
Capacity	15cc/rev
Maximum pressure	35kgf/cm ² (500psi)
Rated oil flow	25.5 l /min(6.7U.S. gpm/5.6U.K. gpm)

4) MAIN CONTROL VALVE

Item	Specification
Type	7 spools
Operating method	Hydraulic pilot system
Main relief valve pressure	330kgf/cm ² (4690psi) [360kgf/cm ² (5120psi)]
Overload relief valve pressure	390kgf/cm ² (5550psi)

[]: Power boost

5) SWING MOTOR

Item	Specification
Type	Axial piston motor
Capacity	250cc/rev
Relief pressure	260kgf/cm ² (3700psi)
Braking system	Automatic, spring applied hydraulic released
Braking torque	107kgf · m(773lbf · ft)
Brake release pressure	30~50kgf/cm ² (427~711psi)
Reduction gear type	2 - stage planetary

6) TRAVEL MOTOR

Item	Specification
Type	Variable displacement axial piston motor
Relief pressure	360kgf/cm ² (5120psi)
Capacity(max / min)	114.2/185.2cc/rev
Reduction gear type	3-stage planetary
Braking system	Automatic, spring applied hydraulic released
Brake release pressure	8.5kgf/cm ² (121psi)
Braking torque	44.4kgf · m(321lbf · ft)

7) REMOTE CONTROL VALVE

Item		Specification
Type		Pressure reducing type
Operating pressure	Minimum	6.5kgf/cm ² (92psi)
	Maximum	26kgf/cm ² (370psi)
Single operation stroke	Lever	61mm(2.4in)
	Pedal	123mm(4.84in)

8) CYLINDER

Item		Specification
Boom cylinder	Bore dia × Rod dia × Stroke	∅ 160 × ∅ 110 × 1500mm
	Cushion	Extend only
Arm cylinder	Bore dia × Rod dia × Stroke	∅ 170 × ∅ 120 × 1760mm
	Cushion	Extend and retract
Bucket cylinder	Bore dia × Rod dia × Stroke	∅ 150 × ∅ 105 × 1295mm
	Cushion	Extend only

※ Discoloration of cylinder rod can occur when the friction reduction additive of lubrication oil spreads on the rod surface.

※ Discoloration does not cause any harmful effect on the cylinder performance.

9) SHOE

Item		Width	Ground pressure	Link quantity	Overall width
R370LC-7	Standard	600mm(24")	0.66kgf/cm ² (9.39psi)	51	3340mm(10' 11")
	Option	700mm(28")	0.57kgf/cm ² (8.11psi)	51	3440mm(11' 3")
		750mm(30")	0.54kgf/cm ² (7.68psi)	51	3490mm(11' 5")
		800mm(32")	0.50kgf/cm ² (7.11psi)	51	3540mm(11' 7")
		900mm(36")	0.45kgf/cm ² (6.40psi)	51	3640mm(11' 11")

10) BUCKET

Item		Capacity		Tooth quantity	Width	
		SAE heaped	CECE heaped		Without side cutter	With side cutter
R370LC-7	Standard	⊙1.62m ³ (2.12yd ³)	1.40m ³ (1.8yd ³)	5	1545mm(60.8")	-
	Option	1.15m ³ (1.50yd ³)	1.0m ³ (1.3yd ³)	4	1090mm(42.9")	1220mm(48.0")
		1.46m ³ (1.91yd ³)	1.27m ³ (1.66yd ³)	4	1380mm(54.3")	1510mm(59.4")
		1.62m ³ (2.12yd ³)	1.40m ³ (1.8yd ³)	5	1440mm(56.7")	1570mm(61.8")
		◆1.62m ³ (2.12yd ³)	1.40m ³ (1.8yd ³)	5	1540mm(60.6")	-
		⊙1.44m ³ (1.88yd ³)	1.27m ³ (1.66yd ³)	5	1280mm(50.4")	-
		⊙1.86m ³ (2.43yd ³)	1.60m ³ (2.1yd ³)	5	1725mm(67.9")	-
		1.86m ³ (2.43yd ³)	1.60m ³ (2.1yd ³)	5	1620mm(63.8")	1750mm(68.9")
		2.10m ³ (2.75yd ³)	1.80m ³ (2.4yd ³)	6	1810mm(71.3")	1940mm(76.4")
		2.32m ³ (3.03yd ³)	2.0m ³ (2.6yd ³)	6	1990mm(78.3")	2120mm(83.5")

◆ : Heavy duty bucket

⊙ : Rock bucket