

2. TIGHTENING TORQUE

Use following table for unspecified torque.

1) BOLT AND NUT

(1) Coarse thread

Bolt size	8T		10T	
	kgf · m	lbf · ft	kgf · m	lbf · ft
M 6 × 1.0	0.85 ~ 1.25	6.15 ~ 9.04	1.14 ~ 1.74	8.2 ~ 12.6
M 8 × 1.25	2.0 ~ 3.0	14.5 ~ 21.7	2.73 ~ 4.12	19.7 ~ 29.8
M10 × 1.5	4.0 ~ 6.0	28.9 ~ 43.4	5.5 ~ 8.3	39.8 ~ 60
M12 × 1.75	7.4 ~ 11.2	53.5 ~ 79.5	9.8 ~ 15.8	71 ~ 114
M14 × 2.0	12.2 ~ 16.6	88.2 ~ 120	16.7 ~ 22.5	121 ~ 167
M16 × 2.0	18.6 ~ 25.2	135 ~ 182	25.2 ~ 34.2	182 ~ 247
M18 × 2.5	25.8 ~ 35.0	187 ~ 253	35.1 ~ 47.5	254 ~ 343
M20 × 2.5	36.2 ~ 49.0	262 ~ 354	49.2 ~ 66.6	356 ~ 482
M22 × 2.5	48.3 ~ 63.3	350 ~ 457	65.8 ~ 98.0	476 ~ 709
M24 × 3.0	62.5 ~ 84.5	452 ~ 611	85.0 ~ 115	615 ~ 832
M30 × 3.5	124 ~ 168	898 ~ 1214	169 ~ 229	1223 ~ 1655
M36 × 4.0	174 ~ 236	1261 ~ 1703	250 ~ 310	1808 ~ 2242

(2) Fine thread

Bolt size	8T		10T	
	kgf · m	lbf · ft	kgf · m	lbf · ft
M 8 × 1.0	2.17 ~ 3.37	15.7 ~ 24.3	3.04 ~ 4.44	22.0 ~ 32.0
M10 × 1.25	4.46 ~ 6.66	32.3 ~ 48.2	5.93 ~ 8.93	42.9 ~ 64.6
M12 × 1.25	7.78 ~ 11.58	76.3 ~ 83.7	10.6 ~ 16.0	76.6 ~ 115
M14 × 1.5	13.3 ~ 18.1	96.2 ~ 130	17.9 ~ 24.1	130 ~ 174
M16 × 1.5	19.9 ~ 26.9	144 ~ 194	26.6 ~ 36.0	193 ~ 260
M18 × 1.5	28.6 ~ 43.6	207 ~ 315	38.4 ~ 52.0	278 ~ 376
M20 × 1.5	40.0 ~ 54.0	289 ~ 390	53.4 ~ 72.2	386 ~ 522
M22 × 1.5	52.7 ~ 71.3	381 ~ 515	70.7 ~ 95.7	512 ~ 692
M24 × 2.0	67.9 ~ 91.9	491 ~ 664	90.9 ~ 123	658 ~ 890
M30 × 2.0	137 ~ 185	990 ~ 1338	182 ~ 248	1314 ~ 1795
M36 × 3.0	192 ~ 260	1389 ~ 1879	262 ~ 354	1893 ~ 2561

2) PIPE AND HOSE

Thread size	Width across flat(mm)	kgf · m	lbf · ft
1/4"	19	3	21.7
3/8"	22	4	28.9
1/2"	27	5	36.2
3/4"	36	12	86.8
1"	41	14	101

3) FITTING

Thread size	Width across flat(mm)	kgf · m	lbf · ft
1/4"	19	4	28.9
3/8"	22	5	36.2
1/2"	27	6	43.4
3/4"	36	13	94.0
1"	41	15	109

4) TIGHTENING TORQUE OF MAJOR COMPONENT

No.	Items	Size	kgf · m	lbf · ft	
1	Engine	Engine mounting bolt, nut	M20 × 2.5	57.9 ± 8.7	419 ± 63
2		Radiator mounting bolt, nut	M12 × 1.75	12.3 ± 2.5	89.0 ± 18
3		Fuel tank mounting bolt	M20 × 2.5	57.9 ± 8.7	419 ± 63
4	Hydraulic system	Main pump housing mounting bolt	1/2-13UNC	12.8 ± 3	92.6 ± 22
5		Steering pump housing mounting bolt	1/2-13UNC	12.8 ± 3	92.6 ± 22
6		Main control valve mounting bolt	M12 × 1.75	12.8 ± 3	92.6 ± 22
7		Steering unit mounting bolt	M10 × 1.5	6.9 ± 1.4	49.9 ± 10
8		Flow amplifier mounting bolt	M10 × 1.5	6.9 ± 1.4	49.9 ± 10
9		Brake valve mounting bolt	M 8 × 1.25	2.5 ± 0.5	18.1 ± 3.6
10		Cut-off valve mounting bolt	M 8 × 1.25	2.5 ± 0.5	18.1 ± 3.6
11		Remote control lever mounting bolt	M 6 × 1.0	1.1 ± 0.2	8.0 ± 1.4
12		Pilot supply unit mounting bolt	M 8 × 1.25	2.5 ± 0.5	18.1 ± 3.6
13		Safety valve	M 8 × 1.25	2.5 ± 0.5	18.1 ± 3.6
14		Hydraulic oil tank mounting bolt	M20 × 2.5	57.9 ± 8.7	419 ± 63
15	Power train system	Transmission mounting bolt	M22 × 2.5	48.0 ± 2	347 ± 14
16		Front axle mounting bolt	M33 × 2.0	225 ± 25	1627 ± 181
17		Rear axle support mounting bolt, nut	M33 × 2.0	225 ± 25	1627 ± 181
18		Tire mounting nut	M22 × 1.5	48.5 ± 2.5	351 ± 18
19		Drive shaft joint mounting bolt, nut	1/2-13UNC	12.3 ± 2	89.0 ± 14
20	Others	Counterweight mounting bolt	M30 × 3.5	199 ± 29.9	1439 ± 216
21		Operator's seat mounting bolt	M 8 × 1.25	3.4 ± 0.8	24.6 ± 5
22		ROPS Cab mounting bolt(4EA)	1.25-12UNF	126	910